

DECLARATION OF PERFORMANCE



042DPE-2013-06-30

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product

Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$, TYPE PORCELAIN TILE

2. Intended use (s)

For internal and external walls and floorings

3. Name or registered trade mark, and contact address of the manufacturer

CERAMICAS APARICI, S.A.
Ctra. Castellón-Alcora, km 12
12130 San Juan de Moró (Castellón) SPAIN

4. System (s) of assessment and verification of constancy of performance

System 4

5. Name and identification number of notified laboratory, if relevant
N/A

6. Declared performances.

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A1 _{FL} /A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD (*)	
- Lead	NPD (*)	
Breaking strength		
- Thickness $\geq 7,5$ mm	>1.300 N	
- Thickness < 7,5 mm	>700 N	
Slipperiness	NPD (*)	
Tactility	NPD (*)	
Bond strength/Adhesion, only for wall tiles:		
- cementitious adhesives type C2	>1 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
- internal uses	Pass	
- external uses: freeze-thaw resistance	Pass	


(*) Performance not declared

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

In San Juan de Moró (Castellón) Spain
June, 30 2013



Mr. Ricardo Aparici Edo